

Dielines created as a Layer in design applications can be removed with SPOT color replacement in Color Centro

- 1. Open Colour Centro
- 2. Select **SPOT COLOUR**



- Browse the Controller folder to find the Spot
 Color Tables and Create a New Table.
 Name it 'Dielines'
- Open the table and click {here} to create a NEW substitute value.
- 5. **NOTE: this name must match the named** color of your file's actual 'die-line'.
- 6. Save this Color.
- Open Settings menu from your print file in FLUX or Print Manager and select the Color Mangement tab.
- 8. Open Manual Settings
- 9. Go to **Optional Settings**
- 10. Select **Spot Colour** with a check mark
- 11. Choose 'Dielines'
- 12. The named colour 'dieline' in the printed file will now be substituted with CMYK set to 0.
- 13. Dielines will removed from the printed output.





	stom settings													
ieneral	Output	Layout	Cover	Finishing	Quality	Image S	icreen	Color mode	Printed items	Forms	Workflov	Color m	anagement)
Color	managen	ent												
You	r can conf	gure the o	default se	ettings for p	rinter color	managem	ent in t	he printer con	figuration, and j	ou can ca	nfigure the	settings fo	individual	paper types in
🔿 Pri	nter defau	lt												
⊖ Imi	age contro	ller color	configur	ation										
💿 Ma	nual setti	ngs												
Verify se	ettings													
	. CHY	(APr	inter pro	file 🔞 Or	tional sett	ines								
RGB				<u> </u>										
RGB	Contraction of the													
RGB	al setting	ţs.												
Option	al setting	ts ngs (Contr	oller con	figuration)										
Option	al setting	şs ıgs (Contr	oller con	figuration)										

